

37-3C-High- voltage tester



High voltage tester 37-3C manually adjustable

- Test voltage 0 .. 2,500/5,000 VAC potential-free
- Tripping current 0 .. 100 mA

37-3C-High- voltage tester

- Test time 1 .. 99s
 - "Burn" function
 - ELABO System 266
-

HV test

- Voltage manually adjustable: potentialfrei
 - Test voltage (general): 0 .. 2.500 / 5.000 VAC
 - Tripping current: 0 .. 100 mA
 - Tripping current manually adjustable
 - Test time: 1 .. 99 s
 - Burn mode
 - Output power: 500 VA
 - Contact monitoring by reading the minimum current
-

Display / Operation

- Combined instrument (digital) for test voltage and test current, switch-selectable
 - Test time setting via code buttons (decade)
-

Interfaces

- digital interface
 - digital-/ analog interface
 - Analog output
-

Equipment data

- Mains voltage: 0 - 230 +10% -5% (49 .. 61 Hz)
 - Safety class: I
 - Slide in technique: ELABO System 266 / 2 WU
 - Height
-

Extensions / Options

- Factory calibration certificate (optional)
-

Order data

- Order description: High- voltage tester
 - Order number: 37-3C.3
-

-bestellzubehoer- (1)

- Order description: High-voltage test probes 2m, 2 items
- order number: 94-2A