

Article No. K0-...

Primus One

System tables



Highlights

- Rear table legs as system profile column with integrated cable duct
- Centrally positioned lowerable cable flap
- Large-volume cable with access from front
- With tables arranged in a row, option of feed-through cabling, level adjuster to compensate floor unevenness
- Optionally with height adjustment – can also be retrofitted
- Possibility of customized color scheme
- System column expandable at the rear
- Front table legs can be moved back for more legroom
- ESD variant for EPA systems

Scope of delivery

System table with cable flap and cable trough

Accessories

Profile panels in the colors traffic red (RAL 3020), signal blue (RAL 5005), black gray (RAL 7021)

Other colors available at extra charge

Socket outlet inserts, table supports, under-table cabinets, safety modules, profile panels with socket outlets, PC holder

Artikel-Nr. K0-...

Primus One System tables

Recommended additional products:

Table racks, shelf boards

Technical Data

Table top	
Thickness	30mm
Front edges	S-edge strip 3mm thick F-Flexi-Line edge, exchangeable
Finish	HPL laminate 0.8mm, glare-free, abrasion-resistant to EN 438, heat-resistant for short period, flame-resistant
Color	Light gray RAL 7035
Cable duct	
Dimensions	Height 145mm, depth 170mm
Cable flap	
Design	Retractable, with brush strip on rear side
Dimensions	W = 880mm, D = 124mm
Loading capacity	
Weight load	200kg surface load
ESD variant	
Table top	As standard design, but also volume-conductive
Design according to	DIN EN 61340-5-1 Part 5-1
Dimensions	
Widths	1200 / 1500 / 1600 / 1800 / 2000mm
Depths	800 / 900 / 1000mm
Height	750mm
	MA = Manual from 750–1050mm
	EM = Electric from 750–1030mm

Accessories

	Order no.
Primus One cable duct cover for covering from the side	K9-0A
Primus One bridge for the connection between two cable ducts for tables in a row	K9-0B
PC-bracket for fixing on the table leg (left and right side). The brightness of the bracket is movable from 160m to 220m for adaption of several Pc's. Max load 15kg.	78-3T
For mounting at any height onto the facing side or side of the InForm profile, for monitors up to 10kg 1 VESA adapter 75/100 for monitor installation 2 horizontal swivel joints 1 spherical head	P3-5K
Socket set for cable duct 2 multiple socket with holder and connection line (for Tables widths of up to 1500mm) 2 multiple socket with holder and connection line (for Tables widths of up to 1600mm)	81-2X Z01 81-2X Z02