

F1-1D-

**HighPerformance**

**High voltage tester F1-1D
fully electronic, modularly expandable**

F1-1D-

- Test voltage 0 .. 6,000/12,000 VAC
potential-free
- Tripping current 0 .. 1/10/40 mA

Available expansion modules:

- Measurement of insulation resistance (option)
- Test voltage 0 .. 8,000/16,000 VDC (option)
- Additional digital outputs (option)

HV test

- Voltage floating
- Test voltage (general): 300 .. 6.000 / 12.000 VAC
- Ramp function: 10 .. 3500 V/s
- Tripping current: 0 .. 1/10/40 mA
- Tripping current programmable
- Active current filter/display
- Delta - I Detection
- Test time: 0.5 .. 999.9 s
- Output power: 500 VA
- Contact monitoring by reading the minimum current
- Output voltage synchron to mains
- Suitable for high voltage test with item under operation (HV-Warm)

Display / Operation

- switchable to national language
- Touch Display 6,5" Color

Interfaces

- ethernet-interface (optional)
- RS 232C-interface
- USB-interface (optional)

Equipment data

- Mains voltage: 230 +/- 10%
- Safety class: I
- Slide in technique: 19"
- Height : 8 HE

Extensions / Options

- Factory calibration certificate (optional)
- Extension module with 6 digital outputs (optional)
- Extension Module Insulation resistance test - (DC required) (optional)
- Extension Module 500 .. 8.000 / 16.000 VDC (optional)
- Extension Module Ethernet (alternative interface) (optional)
- Extension Module USB (alternative interface) (optional)

Order data

- Order description: High Voltage Tester



F1-1D-

- Order number: F1-1D.3